11449

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

CAUTION

Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.

Radio direction finder bearings to commercial broadcasting stations are subject to error and should be used with caution.

Station positions are shown thus:
⊙(Accurate location) ⊕(Approximate location)

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area — — — — — —
Cable Area — — — — — —

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging or trawling.

Covered wells may be marked by lighted or unlighted buoys.

NOTE X

Within the 12-nautical mile Territorial Sea, established by Presidential Proclamation, some Federal laws apply. The Three Nautical Mile Line, previously identified as the outer limit of the territorial sea, is retained as it continues to depict the jurisdictional limit of the other laws. The 9-nautical mile Natural Resource Boundary off the Gulf coast of Florida, Texas, and Puerto Rico, and the Three Nautical Mile Line elsewhere remain in most cases the inner limit of Federal fisheries jurisdiction and the outer limit of the jurisdiction of the states. The 24-nautical mile Contiguous Zone and the 200-nautical mile Exclusive Economic Zone were established by Presidential Proclamation. Unless fixed by treaty or the U.S. Supreme Court, these maritime limits are subject to modification.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.495" northward and 0.746" eastward to agree with this chart.

Mercator Projection
Scale 1:40,000 at Lat. 24°50'
North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

TIDAL INFORMATION

Place		Height referred to datum of soundings (MLLW)			
		Mean High Water	Mean High Water	Mean Low Water	Extreme Low Water
Name	(LAT./LONG)	feet	feet	feet	feet
Indian Key Anchorage, Lower Matecumbe Key	(24°52'N/80°42'W)	2.2	2.1	0.2	-1.1

Note: In the eastern part of Florida Bay, the periodic tide has a mean range less than one-half foot.

(Oct 2006)

HEIGHTS

Heights in feet above Mean High Water.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Key West, FL	WXJ-95	162.40 MHz
Teastable Key, FL	WWG-60	162.45 MHz

THE NATION'S CHARTMAKER SINCE 1807

FLORIDA

INTRACOASTAL WATERWAY

MATECUMBE TO GRASSY KEY

Formerly CK&S 851, 1st Ed., Apr. 1959 KAPP 324

HURRICANES AND TROPICAL STORMS

Hurricanes, tropical storms and other severe weather storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris in unknown locations.

Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may have been moved from their charted positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.

Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard unit.

SHOALS AND PASSES

Mariners are advised to use caution. The shoals and passes, as indicated by dark blue areas (▒) and dotted lines, are obtained from reports and are not verified by field surveys.

NOTE Z

NO-DISCHARGE ZONE, 40 CFR 140

All Florida State waters within the Florida Keys National Marine Sanctuary are designated as a No-Discharge Zone (NDZ). Under the Clean Water Act, Section 312, all vessels operating within a No-Discharge Zone (NDZ) are completely prohibited from discharging any sewage, treated or untreated, into the waters. All vessels with an installed marine sanitation device (MSD) that are navigating, moored, anchored, or docked within a NDZ must have the MSD disabled to prevent the overboard discharge of sewage (treated or untreated) or install a holding tank. Regulations for the NDZ are contained in the U.S. Coast Pilot. Additional information concerning the regulations and requirements may be obtained from the Environmental Protection Agency (EPA) web site: http://www.epa.gov/owow/oceans/regulatory/vessel_sewage/.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

NOTE C

EVERGLADES NATIONAL PARK

(protected area: 36 CFR 7.45)

The killing, collecting, or molesting of animals, the collecting of plants, and water-skiing are prohibited by Federal regulations.

HEIGHTS

Heights in feet above Mean High Water.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

POWER CABLES

Overhead power cables run parallel to U.S. Hy No. 1. All clearances are greater than those of the charted fixed bridges.

NOTE D

PROHIBITED AREAS

(Areas to be avoided)

Under the Florida Keys National Marine Sanctuary and Protection Act, Pub. L. 101-605 and IMO advisory SN/Circ.145, these areas are to be avoided by tank vessels and vessels greater than 50 meters in length.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

PARTICULARLY SENSITIVE SEA AREA

This chart falls entirely within the limits of a Particularly Sensitive Sea Area (PSSA). A PSSA is an environmentally sensitive area around which mariners should exercise extreme caution. See U.S. Coast Pilot volumes for information regarding this area.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 4. Additions or revisions to Chapter 2 are published in the Notices to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 7th Coast Guard District in, Miami, FL., or at the Office of the District Engineer, Corps of Engineers in Jacksonville, FL.

Refer to charted regulation section numbers.

SOUNDINGS IN FEET

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 4 for important supplemental information.

LONG KEY VIADUCT
MULTIPLE ARCH (FIXED) BRIDGE
CENTRAL SPAN
VCR. CL. 49 FT.
HORT. CL. 23 FT.

For Symbols and Abbreviations see Chart No. 1

COLREGS: International Regulations for Preventing Collisions at Sea, 1972. Demarcation lines are shown thus: — — — —

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center at 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

Additional information can be obtained at nauticalcharts.noaa.gov.

SOUNDINGS IN FEET

SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

SOURCE			
B1	1990-2014	NOS Surveys	Partial bottom coverage
B2	1970-1989	NOS Surveys	Partial bottom coverage
B3	1940-1969	NOS Surveys	Partial bottom coverage
B4	1900-1939	NOS Surveys	Partial bottom coverage
B5	Pre-1900	NOS Surveys	Partial bottom coverage



CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

This chart is canceled. No new editions will be issued.

17th Ed., Dec. 2005. Last Correction: 8/26/2022. Cleared through:
LNM: 50/22 (12/13/2022). NM: 52/22 (12/24/2022).
To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

CORAL PROPAGATION

Uncharted submerged manmade structures, designed for the purpose of coral propagation, may exist within the limits of this chart, principally in shallow water areas.

FATHOMS	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
FEET	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
METERS	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36

Matecumbe to Grassy Key
SOUNDINGS IN FEET - SCALE 1:40,000

11449