Within the 12-nautical mile Territorial Sea, established by Presidential Proclamation Report all spills of oil and hazardous subsome Federal laws apply. The Three Nautical Mile Line, previously identified as the outer limit of the territorial sea, is retained as it continues to depict the jurisdictional limit of the other laws. The 9-nautical mile Natural Resource Boundary off the Gulf coast PLANE COORDINATE GRID CAUTION 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153). of Florida, Texas, and Puerto Rico, and the Three Nautical Mile Line elsewhere remain in SUBMARINE PIPELINES AND CABLES (based on NAD 1927) most cases the inner limit of Federal fisheries jurisdiction and the outer limit of the jurisdiction of the states. The 24-nautical mile Contiguous Zone and the 200-nautical The Georgia plane coordinate Grid, (east Charted submarine pipelines and submarine zone) is indicated on this chart at 20,000 foot cables and submarine pipeline and cable areas mile Exclusive Economic Zone were established by Presidential Proclamation intervals thus: - +are shown as: ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.) NOAA WEATHER RADIO BROADCASTS Unless fixed by treaty or the U.S. Supreme Court, these maritime limits are subject The last three digits are omitted. The NOAA Weather Radio stations listed UNITED STATES - EAST COAST AERO aeronautical WARNING below provide continuous weather broadcasts Pipeline Area Cable Area The reception range is typically 20 to 40 The prudent mariner will not rely solely on s seconds SEC sector nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at Navigation regulations are published in Chapter 2, U.S. OBSC obscured HURRICANES AND TROPICAL STORMS any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details. GEORGIA LT HO lighthouse Additional uncharted submarine pipelines and Coast Pilot 4. Additions or revisions to Chapter 2 are pub-Oc occulting Hurricanes, tropical storms and other major storms may M nautical mile m minutes cause considerable damage to marine structures, aids to submarine cables may exist within the area of lished in the Notice to Mariners. Information concerning the DIA diaphone this chart. Not all submarine pipelines and subregulations may be obtained at the Office of the Commander, VQ very quick navigation and moored vessels, resulting in submerged debris Darien, Darien River (31°22'N/081°26'W) Wolf Island, South End, Altamaha Sound (31°19'N/081°19'W) ALTAMAHA SOUND F fixed FI flashing (31°22'N/081°26'W) MICRO TR microwave tower Savannah, GA KEC-85 162.400 MHz marine cables are required to be buried, and 7th Coast Guard District in Miami, Florida, or at the Office in unknown locations. SUPPLEMENTAL INFORMATION Ra Ref radar reflector WHIS whistle Mkr marker those that were originally buried may have become exposed. Mariners should use extreme of the District Engineer, Corps of Engineers in Savannah, Charted soundings, channel depths and shoreline may not Hampton River Entrance (31°13'N/081°19'W) R Bn radiobeacon Y yellow Brunswick, GA WWH-39 162.425 MHz Consult U.S. Coast Pilot 4 for important reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may Bottom characteristics: caution when operating vessels in depths of Refer to charted regulation section numbers. supplemental information. Dashes (- - -) located in datum columns indicate unavailable datum values for a tide station. Real-time water level Oys oysters Rk rock water comparable to their draft in areas where Blds boulders gy gray tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.noaa.gov. AIDS TO NAVIGATION have been moved from their charted positions, damaged, sunk, Mercator Projection Scale 1:40,000 at Lat. 31°18' bk broken Cy clay pipelines and cables may exist, and when CAUTION Consult U.S. Coast Guard Light List for extinguished or otherwise made inoperative. Mariners should anchoring, dragging, or trawling.
Covered wells may be marked by lighted or HEIGHTS Grs grass S sand sy sticky not rely upon the position or operation of an aid to navigation. supplemental information concerning aids to Improved channels shown by broken lines are Heights in feet above Mean High Water. Miscellaneous: Wrecks and submerged obstructions may have been displaced North American Datum of 1983 navigation. subject to shoaling, particularly at the edges. AUTHORITIES AUTH authorized Obstn obstruction PD position doubtful Subm submerged from charted locations. Pipelines may have become uncovered RADAR REFLECTORS Hydrography and topography by the National Ocean Service, Coast ED existence doubtful PA position approximate CAUTION Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and Survey, with additional data from the Corps of Engineers, and U.S. Coast Guard. .21. Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
(2) Rocks that cover and uncover, with heights in feet above datum of soundings. Radar reflectors have been placed on many SOUNDINGS IN FEET floating aids to navigation. Individual radar Temporary changes or defects in aids to AT MEAN LOWER LOW WATER COLREGS: International Regulations for Preventing Collisions at Sea, 1972.

Demarcation lines are shown thus: — — reflector identification on these aids has beer omitted from this chart. navigation are not indicated on this chart. See hazards to navigation to the nearest United States Coast Guard SOUNDINGS IN FEET Local Notice to Mariners. Formerly C&GS 575, 1st Ed., Mar. 1927 C-1937-454 KAPP 245 JOINS CHARTS 11510 & 11507 JOINS CHART 11510 508 RIGHT WHALE SEASONAL MANAGEMENT AREA All vessels greater than or equal to 65 feet in length must slow to speeds of 10 knots or less in seasonal management areas. The controlling depth at Mean Lower Low Water was 7 feet for a width of 150 feet from Doboy The project depth is 12 feet from Savanna Consult the U.S. Army Corps of Engineers for controlling depths and U.S. Coast Guard Local Notice to Mariners for other navigation hazard FI G 2.5s 12ft 5M "195" Broadfield EGG HORIZONTAL DATUM O

The horizontal reference datum of this chart is North
American Datum of 1983 (NAD 83), which for charting ourposes is considered equivalent to the World Geodetic System of 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 do not require conversion to NAD 83 for plotting on this chart. SOURCE DIAGRAM The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained ___ by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, <u>United States Coast Pilot.</u> SOURCE A 1990 - 1997 NOS Surveys full bottom coverage (50 CFR 224.105; see note B) B2 1979 - 1989 NOS Surveys partial bottom coverage B4 1900 - 1939 NOS Surveys partial bottom coverage FI G 2.5s 10ft 5M "227A" h 40 RIGHT WHALE CRITICAL HABITAT ecautionary area: 50 CFR 226.203, 224.103c; see note A) ort Frederica National Monument (Oglethorpe Barracks) (landing prohibited) RESTRICTED AREA (50 CFR 224.105; see note B) 470.3 X 780.1 mm JOINS CHARTS 11506 & 11507 25' ്∜ 20' **19'** 45" 30" 15" **18**' 50" JOINS CHART 11506 **81**°10' **SOUNDINGS IN FEET** Published at Washington, D.C. 11508 U.S. DEPARTMENT OF COMMERCE This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence NOAA encourages users to submit inquiries, discrepancies or comments Altamaha Sound 11508 Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm. NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION SOUNDINGS IN FEET - SCALE 1:40,000 NATIONAL OCEAN SERVICE

This chart is canceled. No new editions will be issued.

22nd Ed., Jan. 2011. Last Correction: 8/26/2022. Cleared through:
LNM: 3422 (8/23/2022), NM: 3522 (8/27/2022)
To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).