Formerly C&GS 210, 1st Ed., June 1876 KAPP 2029

THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES - EAST COAST

MAINE

PENOBSCOT BAY

Mercator Projection
Scale 1:40,000 at Lat. 44°08'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

Additional information can be obtained at nauticalcharts.noaa.gov.

TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	LATITUDE LONGITUDE	Mean Higher High Water	Mean High Water	Mean Low Water
		feet	feet	feet
Northeast Harbor (Deer Isle)	(44°14'N/68°16'W)	11.0	10.5	0.4
Bass Harbor	(44°13'N/68°17'W)	10.1	9.7	0.3
Isle Au Haut	(44°04'N/68°38'W)	10.1	9.7	0.3
Vinalhaven	(44°03'N/68°50'W)	10.1	9.7	0.3
Pulpit Harbor	(44°09'N/68°51'W)	10.7	10.2	0.4
Rockland	(44°06'N/69°06'W)	10.6	10.2	0.4

Daytime (---) is located in datum columns indicates unavailable datum values for a tide station. Real-time water levels, tide predictions, and total current predictions are available on the Internet from http://tidesandcurrents.noaa.gov.
(May 2012)

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)
Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical
Al alternating
B black
Bn beacon
C can
DIA diaphone
F fixed
Fl flashing
Mo morse code
N nun
OBSC obscured
Oc occulting
Or orange
Q quick
R red
Ra Ref radar reflector
R Bn radiobeacon
R TR radio tower
Rot rotating
s seconds
SEC sector
St W static-mile
VQ very quick
W white
WHS whistle
Y yellow

Bottom characteristics:

Bldr boulders
Br broken
Cy clay
Co coral
Gr gravel
Grs grass
Gy gray
h hard
M mud
Oys oysters
Pk rock
S sand
so soft
Sh shells
sy sticky

AUTH authorized
ED existence doubtful
Obstn obstruction
Pk position approximate
PD position doubtful
Rep reported
Subm submerged
Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
Rocks that cover and uncover, with heights in feet above datum of soundings.

HEIGHTS
Heights in feet above Mean High Water.

AUTHORITIES
Hydrography and topography by the National Ocean Service, Coast Survey.

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 1 for important supplemental information.

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.291" northward and 1.667" eastward to agree with this chart.

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 1. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 1st Coast Guard District in Boston, MA or at the Office of the District Engineer, Corps of Engineers in Concord, MA.
Refer to charted regulation section numbers.

COLREGS, 80.100 (see note A)
International Regulations for Preventing Collisions at Sea, 1972.
The entire area of this chart falls seaward of the COLREGS Demarcation Line.

NOTE B
RECOMMENDED VESSEL ROUTE
Deep draft vessels entering and departing Penobscot Bay and River are requested to remain within the recommended vessel route. Two-way traffic is possible within all parts of the green-tinted areas. Other vessels, while not excluded, should exercise caution in these areas and monitor VHF channel 16 or 13 for information concerning vessels transiting these areas. See U.S. Coast Pilot 1, Chapter 7.

NOTE C
Within the 12-nautical mile Territorial Sea, established by Presidential Proclamation, some Federal laws apply. The Three Nautical Mile Line, previously identified as the outer limit of the territorial sea, is retained as it continues to depict the jurisdictional limit of the Submerged Lands Act, the National Resources Act, and the Gulf coast of Florida, Texas, and Puerto Rico, and the Navigation Rules and Inland Navigation Rules must cases the inner limit of Federal fisheries jurisdiction and the outer limit of the jurisdiction of the states. The 24-nautical mile Contiguous Zone and the 200-nautical mile Exclusive Economic Zone were established by Presidential Proclamation. Unless fixed by treaty or the U.S. Supreme Court, these maritime limits are subject to modification.

SOURCE DIAGRAM
The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

SOURCE			
A	1990 - 2010	NOS Surveys	full bottom coverage
B1	1970 - 1994	NOS Surveys	partial bottom coverage
B2	1940 - 1989	NOS Surveys	partial bottom coverage
B3	1940 - 1969	NOS Surveys	partial bottom coverage
B4	1900 - 1939	NOS Surveys	partial bottom coverage
B5	Pre - 1900	NOS Surveys	partial bottom coverage

NOTE D
NO-DISCHARGE ZONE, 40 CFR 140
Under the Clean Water Act, Section 312, all vessels operating within a No-Discharge Zone (NDZ) are completely prohibited from discharging any sewage, treated or untreated, into the waters. All vessels with an installed marine sanitation device (MSD) that are navigating, moored, anchored, or docked within a NDZ must have the MSD disabled to prevent the overboard discharge of sewage treated or untreated. Discharge restrictions for vessels for the NDZ are contained in the U.S. Coast Pilot. Additional information concerning the regulations and requirements may be obtained from the Environmental Protection Agency (EPA) web site: https://www.epa.gov/vessels-marinas-and-ports.

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

NOAA WEATHER RADIO BROADCASTS
The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Ellsworth, ME	KEC-93	162.400 MHz
Dresden, ME	WXM-60	162.475 MHz

PLANE COORDINATE GRID
(based on NAD 27)
The Maine state grid, east zone, is indicated by dashed ticks at 10,000 foot intervals thus: +
The last three digits are omitted.

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.
During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

MARINER ACTIVATED SOUND SIGNALS
Sound signals labeled with (MRASS) require user activation. See USCG Light List.

CABLES
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area
Cable Area

Additional uncharted submarine pipelines are submarine cables may exist within the area of this chart. Mariners should exercise caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered wells may be marked by lighted or unlighted buoys.

RACING BUOYS
Racing buoys within the limits of this chart are not shown hereon. Information may be obtained from the U.S. Coast Guard District Offices as racing and other private buoys are not all listed in the U.S. Coast Guard Light List.



CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

This chart is canceled. No new editions will be issued.

31st Ed., Nov. 2017. Last Correction: 7/15/2023. Cleared through:
LNM: 47/23 (11/07/2023), NM: 48/23 (12/02/2023), CHS: 10/23 (15/07/2023)
To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

Penobscot Bay
SOUNDINGS IN FEET - SCALE 1:40,000