
# **BookletChart**<sup>™</sup>



Bering Sea –
St. Lawrence Island to Bering Strait
NOAA Chart 16220

A reduced-scale NOAA nautical chart for small boaters When possible, use the full-size NOAA chart for navigation.



- Complete, reduced-scale nautical chart
- Print at home for free
- Convenient size
- Up-to-date with Notices to Mariners
- Compiled by NOAA's Office of Coast Survey, the nation's chartmaker

Approximate Page	
12 13 14 15	
16 17 18 19	
20 21 22 23	

# Published by the National Oceanic and Atmospheric Administration National Ocean Service Office of Coast Survey

<u>www.NauticalCharts.NOAA.gov</u> 888-990-NOAA

## What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

## What is a BookletChart<sup>™</sup>?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.


Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at <a href="http://www.NauticalCharts.NOAA.gov">http://www.NauticalCharts.NOAA.gov</a>.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

## **Notice to Mariners Correction Status**

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.

For latest Coast Pilot excerpt visit the Office of Coast Survey website at <a href="http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=162">http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=162</a> <a href="http://www.nauticalcharts.noaa.gov/nsd/searchbycharts.noaa



(Selected Excerpts from Coast Pilot)
St. Lawrence Island is in the N part of the Bering Sea about 120 miles S of Bering Strait. In clear weather can be seen from a distance of 30 to 35 miles. From Southeast Cape a ridge of mountains extends in a N direction across the island, and another ridge extends in a N direction from Apavawook Cape to Northeast Cape.
Between these two ridges a deep bight makes in from S, and at its head very low land extends N across the island. The shore

of the E end of the island is generally a low sand beach with outlying rocks; the mountain ridges begin 0.5 to 2 miles back from the beach.

Northeast Cape is low tundra land, with numerous freshwater lakes. The

cape is 2 miles wide to the foot of a mountain that rises abruptly and has a peak that can be seen on a clear day for 35 miles or more. Although the bottom is irregular off the point of the cape, no breakers were noticed while passing it in rough weather. At a point on the N shore 6 miles W of Northeast Cape, breakers extend 1 mile offshore. Apavawook Cape is so rounding that it has no definite point. This entire stretch of coast is a low, narrow strip behind which is a large lagoon. Punuk Islands are a group of three small islands 1.5 miles long. The shores of all the islands are foul. Vessels should approach these islands with caution.

There was, in 1951, a clear approach to good anchorage in N and W weather off **Maknik Lagoon**, NW of Punuk Islands. The anchorage, in 6½ fathoms, is in 63°09'N, 169°15'W, about 1.5 miles off the beach. Maknik Lagoon is behind the low sand barrier beach. Heavy breakers have been observed in the channel between Punuk Islands and Apavawook Cape; vessels should not attempt to pass through.

**Southeast Cape** has a reef extends about 0.5 mile SE from the point. The W point is lower and a reef makes off from the point in a S direction for 2 to 3 miles. The bight between these points is very foul and should be avoided.

**Kialegak Point** is a long sandspit strewn with rocks that extends in an E direction from the highland of the coast. A reef extends S from the S side of the sandspit for about 1 mile. The remains of a native village are on the sandspit.

Northwest Cape is a steep, black bluff and flat on top. A wide sand beach is W of the bluff. Gambell is a native village with a school and a store. In W winds, breakers have been observed that extend 400 yards NW from the NW tip of land about 1.7 miles W of Northwest Cape. The bay, 6 miles SE of Northwest Cape, affords anchorage with protection from S and W winds, in 3 to 9 fathoms; sand and rocky bottom. Several rock pinnacles, the largest of which is 25 feet high, are off the SW tangent of Southwest Cape on the E side of the entrance to Murphy Bay. A vessel reported striking a submerged rock about 2 miles offshore at a point about 16 miles NE of Southwest Cape.

A reef, bare at low water, makes off 1 mile in a 220° direction from **Siknik Cape**. The submerged part of this reef extends about 4 miles in a general 175° direction from the bare part. This reef is dangerous, as the water shoals abruptly when approaching the cape.

The rest of the island is generally high and rolling. There are some detached rocks showing off the N shore near **Kookoolik Point** and **Savoonga Point**. It is probable that with care an anchorage may be found almost anywhere around the island, but the shores must be approached with caution.

An aerolight is shown at **Savoonga**. Two white windmills that generate electricity for the village are visible 1.0 mile W of the village. Landing small craft at Savoonga is highly dependent on surf conditions. The best landing point in the vicinity of Savoonga can be found on the SE shore of Koomlangeelkuk Bay.

**Warning** - The soil, surface waters, and vegetation of St. Lawrence Island are potentially contaminated by the microscopic eggs of a parasite that causes a long-term and sometimes fatal infection of the liver known as alveolar hydatid disease. This parasite is unusually common on this island, where it is carried by mice, dogs, cats, and wild foxes. Do not transport these animals under any circumstances from the island to other localities.

# U.S. Coast Guard Rescue Coordination Center 24 hour Regional Contact for Emergencies

RCC Juneau

Commander 17th CG District Juneau, Alaska

(907) 463-2000

2

# **Navigation Manager Regions**



To make suggestions, ask questions, or report a problem with a chart, go to <a href="https://www.nauticalcharts.noaa.gov/customer-service/assist/">https://www.nauticalcharts.noaa.gov/customer-service/assist/</a>

## Lateral System As Seen Entering From Seaward

on navigable waters except Western Rivers



For more information on aids to navigation, including those on Western Rivers, please consult the latest USCG Light List for your area. These volumes are available online at <a href="http://www.navcen.uscg.gov">http://www.navcen.uscg.gov</a>

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm. 172° 30' 10' 50' 30' 20' NOS Survey NOS Survey 1990-2015 B2 1970-1989 NOS Survey 1940-1969 NOS Survey B4 1900-1939 NOS Survey Miscellaneo COAST SURVEY **UNITED STATES** ALASKA - WEST COAST 10 **BERING SEA** ST. LAWRENCE ISLAND TO BERING STRAIT Mercator Projection Scale 1:315,350 at Lat 64°30' North American Datum of 1983 (World Geodetic System 1984) DEPTHS IN METERS AND DECIMETERS 66° AT MEAN LOWER LOW WATER Additional information can be obtained at nauticalcharts.noaa.gov. ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)
Aids to Navigation (lights are white unless otherwise indicated): В2 G green AERO aeronautical Mo morse code R TR radio tower ВЗ IQ interrupted quick Iso isophase LT I/O lighthouse M nautical mile Rot rotating s seconds SEC sector St M statute miles Al alternating N nun B black Bn beacon OBSC obscured Oc occulting SOURCE D C can DIA diaphone Or orange VQ very quick W white WHIS whistle m minutes Q quick The outlined areas represent the limit MICRO TR in crowave towe survey information that has been evalu FI flashing Ra Ref radar refector banded in this diagram by date and ty R Bn radiobeacon Y yellow by the U.S. Army Corps of Engineers Bottom characteristics not shown on this diagram. Refer to C Blos boulders gy gray Cy clay Grs grass M mud S sand sy sticky Hydrography in the area of the Sour-ous Surveys was taken from numerous Russian charts. Sufficient data is no common datum. Investigations reve-AUTH authorized Subm submeraed ED existence doubtful PA position approximate Rep reported 50' 21. Wreck, rock, obstruction, or shoal swept clear to the depth indicated.(2) Rocks that cover and uncover, with heights in feet above datum of soundings. added to many depths to adjust them **AUTHORITIES** Hydrography and topography by the National Ocean Service. Coast Survey, with additional data from the U.S. Coast Guard, Geological Mys Krauze Elevations of rocks, b lights are in meters and re Contour elevation value Survey, and National Geospatial-Intelligence Agency. Ostrov Balka elevations are in meters COPYRIGHT No copyright is claimed by the United States Government under Title 17 U.S.C. However, other nations may claim intellectual property rights on the compilation of data depicting the foreign waters shown on this chart. CAUTION Mys Indreniusa Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.

Radio direction-finder bearings to commercial broadcasting stations are OX HAEB subject to error and should be used with caution.

Station positions are shown thus:


• (Accurate location)


• (Approximate location) WECH ONENOTAL s 64 40 RUSSIAN-ENGLISH TRANSLATIONS English .bank, shoal .small bay, cove Russian Russian Mys (M). English .point, cape 1080 Banka..... Bukhta (B) GENTANTY Ostrov (O) island Gavani .harbor Ozero (Oz) lake Racio Sta .mountain, hill .bay peninsula .sound, strait Poluostrov NOTE C

RECOMMENDED TWO-WAY ROUTES


The two-way routes shown on this sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. CAUTION: Full boptom covered to the sheart are recommended for ships of 400 gross tonnage and upwards. FI 5s 3M Ra Ref Q























































This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left

This is the Last Edition of this chart. It will be canceled on Oct 30, 2024 7th Ed., Dec. 2018. Last Correction: 4/29/2024. Cleared through: LNM: 2124 (5/21/2024), NM: 2224 (6/1/2024), CHS: 0424 (4/26/2024)











## VHF Marine Radio channels for use on the waterways:

**Channel 6** – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

**Channel 16** – Emergency, distress and safety calls to Coast Guard and others, and to initiate calls to other

vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here. Channels 68, 69, 71, 72 and 78A – Recreational boat channels.

**Getting and Giving Help** — Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.

## **Distress Call Procedures**

- Make sure radio is on.
- Select Channel 16.
- Press/Hold the transmit button.
- Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of

Emergency; Number of People on Board.

- · Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!



NOAA Weather Radio All Hazards (NWR) is a nationwide network of radio stations broadcasting continuous weather information directly from the nearest National Weather Service office. NWR broadcasts official Weather Service warnings, watches, forecasts and other hazard information 24 hours a day, 7 days a week.

http://www.nws.noaa.gov/nwr/

## **Quick References**

Nautical chart related products and information — http://www.nauticalcharts.noaa.gov

Interactive chart catalog — http://www.charts.noaa.gov/InteractiveCatalog/nrnc.shtml

Report a chart discrepancy — http://ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx

Chart and chart related inquiries and comments — http://ocsdata.ncd.noaa.gov/idrs/inquiry.aspx?frompage=ContactUs

Chart updates (LNM and NM corrections) — http://www.nauticalcharts.noaa.gov/mcd/updates/LNM\_NM.html

Coast Pilot online — http://www.nauticalcharts.noaa.gov/nsd/cpdownload.htm

Tides and Currents — http://tidesandcurrents.noaa.gov

Marine Forecasts — http://www.nws.noaa.gov/om/marine/home.htm

National Data Buoy Center — http://www.ndbc.noaa.gov/

NowCoast web portal for coastal conditions — http://www.nowcoast.noaa.gov/

National Weather Service — http://www.weather.gov/

National Hurrican Center — http://www.nhc.noaa.gov/

Pacific Tsunami Warning Center — http://ptwc.weather.gov/

Contact Us — http://www.nauticalcharts.noaa.gov/staff/contact.htm



For the latest news from Coast Survey, follow @NOAAcharts



This Booklet chart has been designed for duplex printing (printed on front and back of one sheet). If a duplex option is not available on your printer, you may print each sheet and arrange them back-to-back to allow for the proper layout when viewing.